The SmartPower Solution

NetFeeler Lite


NetFeeler Lite is designed to detect changes in Temperature, Humidity and Water Level. It is also able to receive alerts from Wireless Smoke and Security Sensors. When an event occurs, NetFeeler Lite will send out notification. NetFeeler Lite can be connect to NetAgent II and Remote Power Manager ("RPM") for environmental detection. These changes will be shown on NetAgent II or RPM web pages and the user can monitor these remotely thru a web browser.

Features

- Able to detect and measure changes in surrounding temperature, humidity and water leve.
- Able to detect presence of smoke and unauthorised access with wireless sensors (sold separately).

Connect to NetAgent II or RPM will enable the following features:

- Allow monitoring of changes in environment through the Internet using a web browser.
- Able to set data update intervals.
- Able to send TRAP notifications.
- Able to send E-mail when an event occurs.
- Support SNMP protocol for NMS, such as HP Openview.
- Support multiple server shutdown for Windows & Linux operating systems.




NetFeeler Lite with RPM


	Temperature
Detection Range	-40 C to +125 C
Accuracy	+/- 1 C
Response Time	10 seconds in moving air
Humidity	
Detection Range	0 to 100% Relative humidity non-
	condensing
Accuracy	+/- 0.5% Relative Humidity
Response Time	15 seconds in moving air
Temperature Range	-40 C to +85 C (-40 F to +185 F)
* Wireless Rage	30 meters clear line of sight



Wireless Smoke Sensor




NetFeeler Lite with NetAgent II





Wireless Security Sensor



NetFeeler Lite with PC